

Part No. 43903

THUNDERBOLT 3 DOCKING STATION

CONNECT DUAL 4K60 DISPLAYS AND PERIPHERALS OVER A SINGLE CABLE



DESCRIPTION

- Connects an HDMI and Thunderbolt 3 display, USB peripherals and power over a single cable
- Supports Ultra HD 4K 60Hz for both displays and even 5K at the Thunderbolt 3 port
- Integrated 5 port USB 3.1 Gen 1 / USB 3.0 SuperSpeed Hub
- USB Power Delivery capable up to 60W
- 2 year warranty

The Lindy Thunderbolt 3 Docking Station is a powerful and multi-functional solution for connecting notebooks and Macbooks to a range of interfaces including dual displays, using a single cable.

Only Thunderbolt 3 with its incredible bandwidth of 40Gbps allows two 4K 60Hz displays simultaneously or even one 5K 60Hz display while outputting video and audio signal at the same time. It is an essential tool for professional creatives to streamline their workflows, whether it is used for photo and video editing, rendering in real-time, 3D graphics, virtual reality or design. Thunderbolt 3 helps to avoid bottlenecks for demanding work in general.

Featuring all the interfaces needed for a standard workstation, the Lindy Thunderbolt 3 Docking Station uses a single cable to connect to a notebook or Macbook to simultaneously provide dual monitor capabilities at 4K60Hz, Power, Gigabit Ethernet, an SD card reader, Audio and a USB 3.1 SuperSpeed hub. The Docking Station also provides up to 60 Watt of power to connected devices and charging to a notebook/Macbook through the Power Delivery port at the same time.

RELATED PRODUCTS

0

THUNDERBOLT 3 DOCKING STATION

SPECIFICATIONS

Interface	Thunderbolt 3 USB Type C to 5 x USB Type A / 1 x Thunderbolt 3 USB Type C / 1 x HDMI / 1 x RJ45 / 1x SD card / 3.5mm Audio
Interface Standard	Thunderbolt 3, USB 3.1 Gen 1 / 3.0, HDMI 2.0, Gigabit LAN, SD 3.0, 3.5mm Audio
Supported Bandwidth	40 Gbps, 10/100/1000 Mbps
Maximum Input Resolution	4096x2160 / 3840x2160@60Hz, 5120x2880@60Hz
Maximum Output Resolution	4096x2160 / 3840x2160@60Hz (simultaneous use), 5120x2880@60Hz (one display only)
Chipset	Intel Alpine Ridge 4C, Parade PS176 (HDMI), TI TPS65983A (PD), Fresco FL1100 (USB Hub), Intel i210 (LAN)
Compatibility	Thunderbolt 3 USB Type C equipped computers
Power Delivery	PD 2.0 up to 60W (20V 3A)
HDCP Support	HDCP 2.2
Supported Audio	Supports audio 2.1 channel
Seperate Audio Ports	-
Special Features	Supports Battery Charging 1.2 (1 Port),

CONNECTORS

Input	1 x Thunderbolt 3 USB Type C (Male)
Output	5 x USB Type A (Female), 1 x Thunderbolt 3 USB Type C (Female), 1 x RJ45 (Female), 1 x HDMI (Female)
Power	5.5/2.5mm DC socket

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	155x85x23mm (6.1x3.35x0.91in)
Housing Material	Aluminium & plastic
Net Weight	0.452kg (1lb)
Operating Temperature	0° - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 70°C (-4°F - 158°F)
Humidity	0 - 90% RH (non-condensing)
Power Requirements	20VDC 6.75A
Colour	Silver & black

MISCELLANEOUS

Packaging Type	Carton Box
Packaging Dimension	295x147x90mm (11.61x5.79x3.54in)
Gross Weight	1.51kg (3.33lb)
Warranty (Years)	2
Certificated	CE, FCC, REACH, RoHS

PURCHASING INFORMATION

No.	43903
EAN	4002888439039

PACKAGING CONTENTS

Thunderbolt 3 Docking Station
0.4m Thunderbolt 3 cable (USB Type C Male to Male)
External Power Supply with DC connector
Power Cable (UK or Schuko) with IEC C5 connector
Lindy Manual