



70908

PCMCIA 32 bit
P&P
2P (ECP/EPP 32FIFO)

Hardware Guide

◆ DESCRIPTION:

The 70908 is 2 port Parallel PCMCIA card which equipped with two ECP/EPP/SPP/BPP IEEE 1284c CENTRONICS Parallel Interface. The 70908 include two 25 pin female connector for peripherals' units with IEEE 1284C C E N T R O N I C S P a r a l l e l I n t e r f a c e .

◆ Check your packing listing:

70908 Card

Print Cable 44PIN TO 25PIN*2 Female one set

Software Driver

Hardware Guide

Installation Guide

◆ Hardware Specification

Parallel Port:

Parallel Chipset: SUN1888, Hardware FIFO are 32Byte FIFO

Compatible chips: with ACC3203, ST-78C36, and HT6535.

IEEE standard: ECP/EPP/SPP/BPP (PS-II) Interface

Max. Speed: Up to 21.4MB/Sec

◆ Hardware installation guide:

- Turn off the power of your computer
- Plug-in the 70908 MIO Parallel Adapter to PCMCIA slot of your NOBOOK
- Add-on the peripheral (Printer, Modem, Scanner... etc.) that you need to this Adapter
- Turn on the power of your computer

◆ TECHNICAL SPECIFICATION:

Compatibility:	-CARD BUS 32Bit for 486/586/Pentium/Pentium-II/ P-III/C5/K6
Operating system:	-WIN 2000,XP
Chips:	-1 x SUN1888

Connections:	- 44PIN TO 2 x 25 Pin D-SUB female Connector parallel
PCB:	- 2 Layer / 120 x 47 mm



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operations.